



Made from durable 0.002" silver high-performance vinyl film over-laminated with 0.004" velvet finish vinyl film, Asset ID Tags have a permanent pressure-sensitive adhesive back for easy application. Your choice of 8 imprint colours: black, red,

burgundy, blue, green, orange, brown, purple. Black consecutive numbering in your choice of 4 sizes. Supplied on convenient sheets in a poly bag.





Supplied on convenient sheets with:

Spec Document 1109 - Asset Control Program Spec Document 1191 - Application Instructions Asset ID Tags Re-Order Forms

## **Asset ID Tag Standard Sizes**

Number	Dimensions	Tags/Sheet
A-6001	1 <sup>1</sup> /2"x <sup>1</sup> /2"	80
B-6002	1 <sup>1</sup> /2"x <sup>3</sup> /4"	60
C-6003	1 <sup>1</sup> /2"x1"	40
C-6004	2"x <sup>3</sup> /4"	48
D-6005	2"x1"	32
E-6006	2"x1 <sup>1</sup> / <sub>4</sub> "	28
F-6007	2"x1 <sup>1</sup> / <sub>2</sub> "	24
E-6008	$2^{1/2}$ " $x^{3/4}$ "	36
F-6009	2 <sup>1</sup> /2"x1"	30
G-6010	2 <sup>1</sup> /2"x1 <sup>1</sup> /2"	18
F-6011	3"x1"	20
G-6012	3"x1 <sup>1</sup> / <sub>2</sub> "	12
H-6013	3"x2"	10
G-6014	3 <sup>1</sup> /2"x1 <sup>1</sup> /2"	12
H-6015	3 <sup>1</sup> /2"x2"	10
I-6016	3 <sup>1</sup> /2"x2 <sup>1</sup> /2"	8
C-6017	1 <sup>1</sup> / <sub>4</sub> "x1 <sup>1</sup> / <sub>4</sub> "	48
E-6018	1 <sup>3</sup> / <sub>4</sub> "x1 <sup>3</sup> / <sub>4</sub> "	20
C-6019	11/4" diameter	48
E-6020	13/4" diameter	20
1		

Other sizes or shapes are available ... phone or fax for a FastQuote.

## **Consecutive Numbering**

123

Other numbering sizes and styles available

## **Asset ID Tags Adhesive Specifications**

Asset ID Tags are manufactured from high-performance cast vinyl premium quality, flexible, opaque solid colour, medium gloss finish.

Caliper, face: 2.1 mil (53 µm) Caliper, adhesive: 1.0 mil (25 µm)

Liner: 78# Bleached Kraft

Physical Properties: 1.0 mil clear permanent acrylic **Dimensional Stability:** Excellent. < 0.015" (0.4mm) Tensile at Yield: 4.0 - 9.0 lb/in (0.7 - 1.7 kg/cm)

Elongation: 50% minimum

Gloss: ~ 90

**Adhesion: 24 hours:** 4.0 lbs/in (700 N/m)

1 week: 4.5 lbs/in (788 N/m)

Flammability: Self Extinguishing

Shelf Life: 1 year

Durability: Vertical Exposure: Up to 7 years **Minimum Application Temperature:** 40°F (4°C) Service Temperature: -50° to 180° F (-45° to 82° C)

(Reasonable range of temperatures which would

be expected under normal environmental

conditions)

Chemical Resistance: Resistant to most mild acids, alkalis and salt

solutions